



INSTITUT PRO TESTOVÁNÍ A CERTIFIKACI, a.s.
třída Tomáše Bati 299, Louky, 763 02 Zlín, Czech Republic
Division CSI – Centre of Civil Engineering



Notified Body No 1023

CERTIFICATE OF CONSTANCY OF PERFORMANCE No 1023-CPR-0705 P

Construction product: **Thermal insulation boards of mineral wool**
TECHNOBLOCK OPTIMA/ THERMOWOOL BLOCK OPTIMA 55 ,
TECHNOBLOCK PROF/ THERMOWOOL BLOCK PROF 65 ,
TECHNOACOUSTIC/ THERMOWOOL ACOUSTIC 40, TECHNOLITE
OPTIMA/ THERMOWOOL LIGHT OPTIMA 35,
TECHNOROOF 50/ THERMOWOOL ROOF PROF 160 ,
TECHNOBLOCK STANDARD/ THERMOWOOL BLOCK STANDARD
45 , TECHNOVENT PROF/ THERMOWOOL FAS STANDARD 100

Product parameters: **Addendum No. 1/1023-CPR-0705P/d**

Placed on the market under the name or trade mark of: **Limited Liability Company “Heat-Insulating Plant «TECHNO»**
Rizdvyana street 300, 18028 Cherkassy, Ukraine

Relevant standard(s): **EN 13162:2012+A1:2015 Thermal insulation products for buildings –**
Factory made mineral wool (MW) products – Specification

Reports No: **753501172/2015, 343505455/2016, 753501172/2015/A,**
343507191/2018, 755200537C/2024

Certificate first issued on: **2015-11-11**

Notified Body No 1023, in compliance with Regulation (EU) No 305/2011 (CPR), attests that:

- All provisions relating to the Assessment and Verification of Constancy of Performance (AVCP) described in Annex ZA of the above harmonized standard(s) under **AVCP System 1** have been applied
- The factory production control conducted by the manufacturer has been assessed to ensure the constancy of performance of the construction product.

The assessment of performance of the construction product and findings from the initial inspection of the manufacturing plant and factory production control are summarized in the above mentioned Report.

This certificate remains valid as long as neither the harmonised standard, the construction product, the AVCP methods, nor the manufacturing conditions in the plant are modified significantly, unless suspended or withdrawn by the Notified Body.



Representative of Notified Body No 1023

Revision d): **2024-05-16**
Replaces the withdrawn certificate 1023-CPR-0705 P (Revision c), issued on 2018-10-24

Addendum No. 1/1023-CPR-0705P/d

Product parameters:

TECHNOBLOCK OPTIMA/ THERMOWOOL BLOCK OPTIMA 55 (thicknesses: 40-200 mm, density:50-60 kg/m³):

RtF:A1. Intended use: Thermal insulation for buildings

TECHNOBLOCK PROF/ THERMOWOOL BLOCK PROF 65 (thicknesses: 40-200 mm, density:60-70 kg/m³):

RtF:A1. Intended use: Thermal insulation for buildings

TECHNOACOUSTIC/ THERMOWOOL ACOUSTIC 40 (thicknesses: 40-200 mm, density:35-45 kg/m³):

RtF:A1. Intended use: Thermal insulation for buildings

TECHNOLITE OPTIMA/ THERMOWOOL LIGHT OPTIMA 35 (thicknesses: 40-200 mm, density:30-40 kg/m³):

RtF:A1. Intended use: Thermal insulation for buildings

TECHNOROOF 50/ THERMOWOOL ROOF PROF 160 (thicknesses: 40-150 mm, density:145-175 kg/m³):

RtF:A1. Intended use: Thermal insulation for buildings

TECHNOBLOCK STANDARD/ THERMOWOOL BLOCK STANDARD 45 (thicknesses: 40-200 mm, density:40-50 kg/m³):

RtF:A1. Intended use: Thermal insulation for buildings

TECHNOVENT PROF/ THERMOWOOL FAS STANDARD 100 (thicknesses: 40-200 mm, density:90-110 kg/m³):

RtF:A1. Intended use: Thermal insulation for buildings

Issued in Zlin on 2024-05-16



Mgr. Jiří Heš

Representative of Notified Body No 1023